



Diesel Generator Set

X2.6 Series

25 - 40 kVA, 20 - 32 kW Prime
CPCB IV+ Emission Compliant



Latest Technology and Unmatched Performance

- The Cummins® X2.6 series rugged engine and world class Stamford alternator powered diesel generator set
- Advanced in-cylinder technology to meet latest emission norms without any after-treatment device
- Best in class transient response
- High altitude capabilities
- Superior finish and aesthetics
- Compact in size with optimum power to weight ratio

Environment Friendly Power

- Class defining technology engine is designed to meet stringent exhaust emission tests as per revised MoEF norms, thus offering environment friendly power
- The Cummins® diesel generator sets are available with the lowest noise levels in its range

Lowest Operating Cost and Comprehensive Warranty

- Highly reliable and durable product
- All elements are designed to work together to maximize efficiency even at part loads, offering the advantage of lowest operating costs
- 500 Hours/18 months service interval
- Industry acknowledged best-in-class comprehensive warranty on the entire package including rubber components

Single Source Power Assurance

- All the major components - the engine, alternator, control system and canopy are designed, manufactured, and tested by Cummins India
- Best and largest customer support network in India, capable of providing round-the-clock service and spares support

Engine

- Cummins® X2.6 series, 3 cylinder, In-line 4 stroke, radiator cooled engine
- Well-designed air handling system with
 - Dry type, replaceable paper element air cleaner with restriction indicator
 - Air to air aftercooling
 - Optimized turbocharger for increased altitude capabilities
- Optimized fuel consumption with
 - Common rail electronic injection
 - Spin on fuel filter
- Standard integral set-mounted radiator system, designed and tested for 50°C ambient temperature
- Full flow spin on lube oil filter
- First fill of lube oil and coolant
- Electrical starter motor with soft start engagement feature
- Battery charging alternator
- 1 X 12 V DC battery



Alternator

- STAMFORD S0L2, S1L2 and S2L1 alternator frames from Cummins Generator Technology
- Brushless type, Screen protected, Revolving field, Self-excited alternator conforming to IS/IEC 60034-1
- Better motor starting capability
- Best in class efficiency
- Compact design with sealed bearings for longer life and lesser maintenance
- Impregnation on all wound components for better mechanical strength

Control Panel

Control panel is manufactured with 14/16-gauge CRCA sheet and is powder coated for weather-proof and long-lasting finish. The control panel consists of the following parts:

- PS0602 Controller
- Aluminum bus bars with suitable capacity with incoming/outgoing terminals
- Indicating lamps for 'Load ON' and 'Set Running' Instrument fuses duly wired and ferruled
- MCCB of suitable rating with short circuit protections
- AC/DC separation inside control panel for safety

PS0602 Features



- Cummins PowerStart™ PS0602 control is a microprocessor- based generator set monitoring and control system. AMF Functionality is inbuilt, and this control includes an intuitive operator interface that allows for complete generator set control as well as system metering, fault annunciation, configuration, and diagnostics
- AMF Functionality
- Electronic Governing
- CAN (J1939) Compatible
- Sync Compatible (Capable to accept external speed signal from 3rd party sync controller)
- Intuitive operator interface which includes LED backlit 128X64 pixel graphic display with tactile feel soft-switches & generator set status LED lamps
- Remote start-stop
- Suitable for FAE based engine architecture
- Engine Metering: Oil pressure, Engine temperature, Starting battery voltage, Engine running hours
- AC Alternator Metering: L-L Voltage and L-N Voltage, Current (phase and total), kVA (phase and total) and Frequency. kwh, Total & per phase (kw & kVA), PF, Utility Voltage and Freq
- Engine Protection: Low lube oil pressure, High/Low coolant temperature, Battery High/Low/Weak Volts, Fail to Crank/Start, Sensor failure, Cranking lockout, Low fuel level.
- AC Alternator Protection: Over/Under Voltage, Over/Under Frequency, Loss of AC sensing. Overspeed, Over Current, kW Overload
- Data Logging: Engine hours, Control hours and upto 5 recent fault codes
- Configurable glow plug control
- 12 Volt DC operation
- Sleep mode
- Modbus interface (RS485 RTU)
- In Power compatible (PC based service tool)
- Certifications - meets the requirement of relevant ISO, EN, Mil Std. and CE standards.
- Maintenance due alarm based on Engine Run Time and due date
- Exerciser scheduler

Silencer

- Critical Grade Silencer suitably optimized to meet stringent sound emission standards laid down by MoEF / CPCB

Mounting Arrangement

- Engine and alternator are mounted on a common MS fabricated base frame with AVM pads
- Skid mounted radiator
- Base frame with integral fuel tank is provided with drain plug, air vent, inlet and outlet connection and provision for cleaning

Optional

- Engine: Cold Start Kit
- Alternator: PMG and Space Heater
- Canopy: Inside bolt design
- Remote monitoring system

Alternator Specification				
Make	STAMFORD (CGT)	STAMFORD (CGT)	STAMFORD (CGT)	STAMFORD (CGT)
Alternator Frame	S0L2-M	S0L2-P	S1L2-J	S2L1D-C41
Enclosure	IP 23	IP 23	IP 23	IP 23
Voltage regulation (Max.)	±1%	±1%	±0.5%	±0.5%
Class of Insulation	H Class	H Class	H Class	H Class
Winding Pitch	2/3	2/3	2/3	2/3
Stator Winding	Double layer lap			
Rotor	Dynamically Balanced			
Waveform distortion/ Total Harmonic Distortion	No load < 1.5 %, Non distorting balanced linear load < 5 %			
Maximum Unbalanced Load across phases*	less than or equal to 25%			
Telephonic Harmonic factor	< 2%			

Rating Definitions	Conformance Standards
<p>Prime Power (PRP): Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528.</p>	<ul style="list-style-type: none"> • IS/IEC 60034-1 • ISO 1460 • ISO 8528 • ISO 3046 • ISO 9001 • ISO 13018

Typical Enclosed Genset Dimensions						
Genset Model	Rating (kVA)	Length (mm)	Width (mm)	Height (mm)	Wet Weight" (kg)	Standard Fuel tank Capacity (litre)
CI 25D5P	25	2400	950	1400	1029	102
CI 30D5P	30	2400	950	1400	1029	102
CI 35D5P	30	2400	950	1400	1065	102
CI 40D5P	40	2400	950	1400	1090	102

"Approximate Weight

Authorised Representative

Cummins Power Systems Offices

Bengaluru: **Tel.:** (080) 2325 9161 / 63, 2325 9165 / 67 | **Fax:** (080) 2325 9164
 Chandigarh: **Tel.:** (0172) 224 0371-73 | **Fax:** (0172) 224 0372
 Chennai: **Tel.:** (044) 2446 8110 / 2446 8113 | **Fax:** (044) 2491 1120
 Gurgaon: **Tel.:** (0124) 391 0900-01 | **Fax:** (0124) 391 0916
 Hyderabad: **Tel.:** (040) 2340 9970 / 2340 9980 | **Fax:** (040) 2340 9990
 Jaipur: **Tel.:** (0141) 236 4944 | **Fax:** (0141) 403 8794
 Kolkata: **Tel.:** (033) 2287 8065 / 2287 2481 | **Fax:** (033) 2290 3839
 Lucknow: **Tel.:** (0522) 230 5049 / 230 5059 | **Fax:** (0522) 230 5035
 Mohali: **Tel.:** (0172) 224 0371 | 72 / 73 | **Fax:** (0172) 224 0371 / 72 / 73
 Vadodara: **Tel.:** (0265) 233 0627 / 3053627 | **Fax:** (0265) 234 0623



Visit our Facebook page at :
Cummins Power Generation India



"Our energy working for you."

Cummins is registered trademarks of Cummins Inc.
Specifications are subject to change without notice.
PSBU/CPCB IV+/X2.6/Rev-00/07 2023



**Cummins India Limited
Power Systems Business**
 Cummins India Office Campus
 Tower-A, 8th Floor, S. No. 21
 Balewadi, Pune - 411 045 (India)
 Email : cpgindia@cummins.com
 www.cummins.com